



## 15 Watt Fixed Wall Plug Series Adapter Meets Level VI Requirements



### Features

- Limited Power Source (LPS)
- Class B EMI
- Level VI Compliant
- Class II Double Insulated
- High Efficiency
- Low Cost

### Applications

- Wireless Communications
- Peripherals
- Portable Equipment
- PDA

### Safety Approvals

- cUL/UL

### Mechanical Characteristics

- Length: 71.7mm (2.82in)
- Width: 50mm (1.97in)
- Height: 33.2mm (1.31in)
- Weight: 145g (5.12oz)

### Output Specifications

Model	DC Output Voltage	Load		Ripple <sup>(1)</sup> P-P (max.)	Regulation Line & Load	Efficiency Level
		Min.	Max.			
PSC15A-050	5V	0A	3.0A	100mV	±5%	VI
PSC15A-060	5.9V	0A	2.5A	100mV	±5%	VI
PSC15A-075	7.5V	0A	2.0A	100mV	±5%	VI
PSC15A-090	9V	0A	1.67A	120mV	±5%	VI
PSA15A-120P6	12V	0A	1.25A	100mV	±5%	VI
PSA15A-150P6	15V	0A	1.0A	100mV	±5%	VI
PSA15A-240P6	24V	0A	0.65A	200mV	±5%	VI
PSA15A-480P6	48V	0A	0.31A	400mV	±5%	VI

(1) Measured after 30 minutes with by-pass capacitors 0.1uF/10uF at output connector terminal and oscilloscope set at 20Mhz.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**Input:**

**AC Input Voltage Rating**  
100 to 240V AC

**AC Input Voltage Range**  
90 to 264V AC

**AC Input Frequency**  
47 to 63Hz

**Input Current**  
0.5A (RMS) maximum at 120V AC  
0.25A (RMS) maximum at 240V AC

**Leakage Current**  
0.25mA maximum at all line conditions

**Inrush Current**  
<40A for 120V AC at maximum load  
<60A for 240V AC at maximum load  
(Cold start at ambient 25°C)

**Input Power Saving**  
0.1W maximum at no load

**Output:**  
**Efficiency**  
US DOE Level VI

**Environmental:**  
**Temperature**  
Operation 0 to +40°C  
Non-operation -40 to +85°C

Humidity 20 to 90%

**Emissions**  
FCC Class B  
EN55022 Class B

**Immunity**  
IEC61000-4-2  
IEC61000-4-3  
IEC61000-4-4  
IEC61000-4-5  
IEC61000-4-6  
IEC61000-4-8  
IEC61000-4-11  
EN61000-3-2

**Hold-up Time**  
8mS minimum at 120V AC and maximum load

**Over-Voltage Protection**  
Zener clamping if voltage exceeds 120% of limit

**Over-Current Protection**  
Output equipped with short circuit protection – auto-restart

**Short-Circuit Protection**  
Output can be shorted without damage

**Dielectric Withstand (Hi-pot) Test**  
Primary to Secondary: 3000V AC for 1 min., 10mA

**DC Output Connector**  
2.1 x 5.5mm Center Positive Barrel

**Dimension Diagram Unit: mm (inch)**

