

Cable tie - PKB 140X3,6 BK - 1005525

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Cable tie, resistant to UV rays, dimensions: L x W, 140 x 3.6 mm, color: black

Product Features

- The plastic cable binders are ideal for use with WMTB, KMK 2, and KMK 4 cable markers from Phoenix Contact
- With the UNIFOX-CT ... cable binder tool, the cable binders can be easily tightened and cut off in one step
- UV stabilized (black), for use in outdoor systems
- The cable binders can be used indoors and outdoors even under unfavorable industrial conditions
- Transparent, for standard applications
- For bundling control lines and cables

Key commercial data

Packing unit	1 PCE
Minimum order quantity	1000 PCE
GTIN	 4 017918 012595
Custom tariff number	39269097
Country of origin	UNITED STATES

Technical data

General

Length (b)	140 mm
Width (a)	3.6 mm
Color	black
Inflammability class according to UL 94	V2
Ambient temperature (operation)	-40 °C ... 85 °C
Material	PA

Cable tie - PKB 140X3,6 BK - 1005525

Classifications

ETIM

ETIM 2.0	EC000046
ETIM 3.0	EC000046
ETIM 4.0	EC000046
ETIM 5.0	EC000046

UNSPSC

UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703
UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703

eCl@ss

eCl@ss 4.0	27140702
eCl@ss 4.1	27140702
eCl@ss 5.0	27140702
eCl@ss 5.1	27140702
eCl@ss 6.0	27140702
eCl@ss 7.0	27140702