



NO.	MASSE / DIMENSION
A	53.4
B	22.2
C	4
D	33.8
E	47.8
F	44.5
G	57
H	4.3

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
5	KONTAKTSTIFT/ CONTACT PIN
8	DOSENGEHÄUSE / SHELL



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate over cadmium (conductive)
Insulator Material:	CR-Elastomere
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm Dimensions without tolerance indications are general tolerances in acc. with DIN7168m		drawing for CUSTOMER				
 ITT <i>Engineered for life</i> <small>ITT CANNON GmbH D - 71384 Weinstadt/Germany</small>		description CA02L32A10P-B Box mounting receptacle				
		PCB Ø 0,76 / Pin / Layout: 32A10				
© All rights reserved. Reproduction or issue to third in any form whatever is only permitted with written authorization of ITT Cannon		<table border="1"> <tr> <td>page</td> <td>revision</td> </tr> <tr> <td>1/2</td> <td>1488 30. Jul 18</td> </tr> </table>	page	revision	1/2	1488 30. Jul 18
page	revision					
1/2	1488 30. Jul 18					