



- NOTES:
1. ALL DIMENSIONS IN MM
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.2
  3. TRAVEL (TOTAL): 2.0 mm
  4. OPERATING FORCE: 50gf Max.
  5. RATING: 12V DC, 100mA (Resistive load)
  6. CONTACT RATING: 80m ohms max.
  7. OPERATING TEMP. -20°C to 80°C
  8. MATERIALS  
HOUSING: 4/6 NYLON  
ACTUATOR: 6T NYLON  
COVER/SPRING: STAINLESS STEEL  
CONTACTS: SILVER PLATED PHOSPHOR BRONZE  
TERMINALS: SILVER PLATED BRASS
  9. PACKAGING: TAPE AND REEL, 1900 PIECES PER REEL.

CONTACT CONFIGURATION  
SPST NORMALLY OPEN (N.O.) CONTACTS

REV.	ECN No.	DESCRIPTION	DATE	CHKD
H	15120	REVISED TERMINAL SHAPE	7/28/05	RC
G	12884	ADD PCB CENTER TO CENTER	3/5/03	CB
F	12751	REVISED, ADD NEW DIM	1/23/03	CB
E	12201	ADD NOTE 8	5/31/02	CB

SCALE	DATE	DR	DWG	REV
8:1	8/24/98	MM		H

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED



900 BG Q