



# Thermofit Molded Parts Specification Control Drawing

Part Number : 602A022  
Description : Transition, 1 To 5

## NOTES

- All dimensions are in  $\frac{\text{inches}}{\text{millimeters}}$
- Dimensions appearing in table are as follows:
  - a - As Supplied
  - b - After Unrestricted Recovery
- Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.



PART NUMBER	H		J		P	R	HW	JW
	Min a	Max b	Min a	Max b	±10% b	±10% b	±20% b	±20% b
602A022	.75 [19,0]	.58 [14,7]	.20 [5,1]	.14 [3,5]	1.68 [42,6]	1.25 [31,7]	.03 [0,76]	.04 [1,01]

If this document is printed it becomes uncontrolled.  
Check for the latest revision.



RAYCHEM CORPORATION  
300 CONSTITUTION DRIVE  
MENLO PARK, CALIFORNIA 94025

Revision : F  
Date : 2/17/99


Part Number : 602A022  
Description : Transition, 1 To 5

# Thermofit Molded Parts Specification Control Drawing

Part Number : 602A022  
Description : Transition, 1 To 5

MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION
-3	Polyolefin, Semi-rigid	RT-301	/42;/86	S-1017;S-1048	Adhesive
-4	Polyolefin, Flexible	RT-1304	/42;/86	S-1017;S-1048	Adhesive
-25	Elastomer, Fluid Resistant	RT-1325	N/A		

## ORDERING INFORMATION



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION



RAYCHEM CORPORATION  
300 CONSTITUTION DRIVE  
MENLO PARK, CALIFORNIA 94025

Revision : F  
Date : 2/17/99

Part Number : 602A022  
Description : Transition, 1 To 5