

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +85°C (NOTE1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60°C
	VOLTAGE	80 V AC	APPLICABLE CONNECTOR	DF24 * - * DS-0.9C
	CURRENT (NOTES 1, 2)	0.3 A	APPLICABLE CABLE INSULATION DIAMETER	AWG 32 TO AWG 34 φ0.6 mm MAX

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

ELECTRIC CHARACTERISTICS

CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000 Hz).	30 mΩMAX.	X	-
--------------------	---------------------------------	-----------	---	---

MECHANICAL CHARACTERISTICS

MECHANICAL OPERATION	30 TIMES INSERTION AND EXTRACTION.	① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
CONTACT INSERTION AND EXTRACTION FORCES	□0.15 mm BY STEEL GAUGE.	① INSERTION FORCE :2.0 N MAX. ② EXTRACTION FORCE:0.12 N MIN.	X	-
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLES FOR 3 DIRECTION.	① NO ELECTRICAL DISCONTINUITY OF 1 μs.	X	-
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
CRIMP TENSILE STRENGTH	Contact is crimped only wire.	① #AWG32 : 5.0 N MIN. ② #AWG34 : 4.0 N MIN.	X	-

ENVIRONMENTAL CHARACTERISTICS

DAMP HEAT(STEADY STATE)	EXPOSED AT 40 ± 2°C , 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→15 TO 35→+85→15 TO 35°C TIME 30→ 2 TO 3 → 30→ 2 TO 3min UNDER 5 CYCLES.		X	-
CORROSION, SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48h.	NO HEAVY CORROSION	X	-
SULPHUR DIOXIDE	EXPOSED IN 25 PPM FOR 96 h. (TEST STANDARD: JIS-C-0090)		X	-

REMARKS

NOTE 1: INCLUDE THE TEMPERATURE RISING BY CURRENT.

NOTE 2: TO REQUIRE THE CURRENT LOCALLY EXCEEDING RATING,EVALUATION IS REQUIRED SEPARATELY.

Unless otherwise specified, refer to JIS C 5402.

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△				
		APPROVED	TY.OMA	05.07.29
		CHECKED	HK.UMEHARA	05.07.29
		DESIGNED	TS.KUMAZAWA	05.07.29
		DRAWN	FK.MATSUKI	05.07.21

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-303437-01
--	-------------	----------------

HRS	SPECIFICATION SHEET	PART NO.	DF24-3234SCFA	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL687-3004-0-00	△ 1/