


Wire-wound Chip Power Inductors (BR series)[BRC]

BRC1608TR60M6



■ Features

- Item Summary
0.6uH±20%, 0.94A, 0603/1608 (EIA/JIS)
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping Embossed 3000pcs

■ Products characteristics table

Inductance	0.6 uH ± 20 %
Case Size (EIA/JIS)	0603/1608
Rated Current (max)	0.94 A
Saturation Current (max)	1.1 A
Temperature Rise Current (max)	0.94 A
DC Resistance (max)	128.7 mΩ
DC Resistance (typ)	99 mΩ
LQ Measuring Frequency	6 MHz
Self Resonant Frequency (min)	630 MHz
Operating Temp. Range	-40 to +105 °C (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 15 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

■ External Dimensions

Dimension L	1.6 ±0.2 mm
Dimension W	0.8 ±0.2 mm
Dimension T	0.8 ±0.2 mm
Dimension e	0.45 ±0.15 mm

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.

Wire-wound Chip Power Inductors (BR series)

BRC1608TR60M6






Dimension	unit : mm	unit : inch
Length :	1.6 +/- 0.2	(0.063 +/- 0.008)
Width :	0.8 +/- 0.2	(0.031 +/- 0.008)
Height :	0.8 +/- 0.2	(0.031 +/- 0.008)

Inductance :	0.60	uH	(test freq at 6MHz)
DC Resistance :	0.099 / 0.1287	ohm	(typ / max)
Saturation Current :	1,100	mA	
Temp. rise Current :	940	mA	

Saturation current typical : 30% reduction from initial L value.

Temp rise Current typical : Temperature will rise by 40 deg C



The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the data at any time without notice. Before making final selection, please check product specification.