

172x51mm

AC AXIAL FAN

FDA2-R17251-SF Series



Features:

- Motor: External Rotor Capacitor-Run Induction Motor
- Motor Protection: Thermal Protected
- Bearing Type: Two Ball
- Connection: UL 1015 AWG 22, 300mm Wire Leads or Terminal
- Frame Material: Aluminum Alloy
- Impeller Material: Plastic UL94V-0, or Steel
- **Salt Fog Rated - GR-487-CORE, ASTM B117-11, ISO 9227 Compliant**
- **IP56M Certified**
- Operating Temp:
Two Ball: -20°C~70°C
- Life Expectancy:
Two Ball: 70,000 Hours



SALT FOG

Fan-S Division



Model No.	Volt.	Freq.	Current	Power	Rated Speed	Maximum AirFlow		Maximum Static Pressure		Noise Level	Weight
	(VAC)	(Hz)	(A)	(W)	(rpm)	(CMM)	(CFM)	(InAq)	(mmAq)	(dB/A)	(g)
FDA2-R17251NBK ** F-SF	115	50/60	0.27/0.23	26.0/26.0	2800/3300	6.51/7.65	230/270	0.649/0.787	16.5/20.0	55.0/61.0	1080
FDA2-R17251QBK ** F-SF	230	50/60	0.10/0.11	23.0/26.0	2800/3300	6.51/7.65	230/270	0.649/0.787	16.5/20.0	55.0/61.0	1080

* Indicates "W" (Wire Leads) or "T" (Terminal)

Noise is measured at the distance of one (1) meter from the axis of intake.

** Indicates "3" (Metal Frame, Plastic Impeller) or "4" (Metal Frame and Impeller)

