

## TERMOPTO TOS 120VAC/48VDC 0.5A RC

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



TERMOPTO solid-state relay, 5 to 48 V DC 0.5 A output version,

with AC or DC input, available in different versions:

- With screw connection
- In 6.1 mm width
- With various input protective circuits (free-wheel diode, varistor, RC filter)
- Pluggable cross-connections
- Enclosed design

### General ordering data

Order No.	<a href="#">1180290000</a>
Type	TOS 120VAC/48VDC 0.5A RC
Version	TERMOPTO, Solid-state relay, Rated control voltage: 120 V AC $\pm 20\%$ , Rated switching voltage: 5...48 V DC, Rated switching current: 500 mA, Screw connection
GTIN (EAN)	4032248100057
Qty.	10 pc(s).

**TERMOPTO**  
**TOS 120VAC/48VDC 0.5A RC**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

Width	6.1 mm	Height	74.5 mm
Depth	55 mm	Net weight	20.6 g

**Temperatures**

Operating temperature	-20 °C...+60 °C	Storage temperature	-40 °C...+80 °C
-----------------------	-----------------	---------------------	-----------------

**Probability of failure**

MTTF	2,500 Years
------	-------------

**Connection data**

Clamping range, rated connection	2.5 mm <sup>2</sup>	Clamping range, rated connection, min.	0.5 mm <sup>2</sup>
Clamping range, rated connection, max.	4 mm <sup>2</sup>	Tightening torque, min.	0.4 Nm
Tightening torque, max.	0.6 Nm	Stripping length, rated connection	9 mm

**Control side**

Rated control voltage	120 V AC ±20 %	Nominal control current	6.4 mA AC
Power rating	≤ 0.61 VA	Input frequency	< 10 Hz
Cut-in (switch-on) voltage	≥ 102 V AC	Dropout voltage	≤ 48 V AC
Protective circuit, control side	RC element	Status display on control side	Green LED

**Load side**

Rated switching voltage	5...48 V DC	Continuous current	500 mA
Rated switching current	500 mA	Switch-on delay	< 12.6 ms
Switch-off delay	< 20.8 ms	Load category	DC1
Leakage current	< 10 µA	Protective circuit, load side	Diode
Voltage drop at max. load	< 1 V	Load side status indicator	No
Short-circuit-proof	No		

**General data**

Solid-state type	Transistor	No. of poles	1
Conductor connection system	Screw connection	Humidity	5...95 % rel. humidity T <sub>u</sub> = 40 °C, no condensation
UL 94 flammability rating		V-0	Standards

**Insulation coordination**

Rated voltage	300 V	Clearance and creepage distances for control side - load side	> 3 mm
Impulse withstand voltage	4 kV (1.2/50 µs)	Pollution severity	2
Surge voltage category	III		

**Further details of approvals**

Standards	DIN EN 50178, IEC 62314, UL508
-----------	--------------------------------

**TERMOPTO  
TOS 120VAC/48VDC 0.5A RC**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data****Classifications**

ETIM 3.0	EC001504	eClass 5.1	27-27-09-90
eClass 6.0	27-27-09-90	eClass 7.0	27-27-09-90

**Approvals**

Approvals

**Downloads**Declaration of Conformity [K305\\_02\\_11.pdf](#)

**TERMOPTO  
TOS 120VAC/48VDC 0.5A RC**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Drawings****Electric symbol****120 V...230 V AC**