


A



Extended length is with 500g of force


B

C

D

E

F



SBC: A-A

P1	COLOR
1	WHITE
2	BLACK
3	RED
4	GREEN
5	YELLOW
6	BLUE

Extended Length ("L2")	Typical Retracted Length ("L1")
60.0 Inches - 69.0 Inches	21.5 Inches
1,524.0MM-1,752.6MM	546.1MM

**Material:**

- Plug Housing: Polycarbonate, clear
- Plug Terminal: 0.36"[0.14MM] Thick Phosphor Bronze
- Connector: 50µm of Selective Gold Contact Plating
  - Area, Gold flash over the remainder
  - Over 2.54µm[0.00100] thick nickel underplate
- Conductor(X6C): 26AWG (0.12X12) Bare Copper
- Insulation(X6C): PP6331 ID 0.95-1.0
- Jacke: PVC No UL 80 P
- Package: Individual PE Bag

G

H



Scale	1:1						Name	Item No.
TOLERANCE					Drawn	11.02.11	Chappell	<b>AT-C-26-6/6/S-5-OE</b>
X.X	±0.40				Approved			
X.XX	±0.25							Drawing No.
X.XXX	±0.15							<b>rev00</b>
Angle	±3°							Sheet
		Modification	Date	Name	<b>ASSMANN</b> W+S+W components			Replace