

Flush-type connector - SACC-DSI-MINMS-5CON-UNF PCB - 1457487

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Sensor/actuator flush-type plug, 5-pos., 7/8", PCB mounting with 7/8" fastening thread

The illustration shows the 3-pos. version



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 616997
GTIN	4046356616997

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C (Plug)
Degree of protection	IP67

General

Rated current at 40°C	9 A
Rated voltage	250 V
Number of positions	5
Insulation resistance	≥ 100 MΩ
Coding	A - standard
Status display	No
Overvoltage category	II
Degree of pollution	3
Connection method	Solder pins
Mounting type	PCB mounting 7/8"

Material

Flammability rating according to UL 94	HB
--	----

Flush-type connector - SACC-DSI-MINMS-5CON-UNF PCB - 1457487

Technical data

Material

Contact material	CuZn
Contact surface material	Au
Contact carrier material	PUR
Material, knurls	Zinc die-cast, nickel-plated
Sealing material	Viton

Standards and Regulations


Connection in acc. with standard	CUL
Flammability rating according to UL 94	HB

Environmental Product Compliance


China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing




Schematic diagram




Connector pin assignment

Drilling diagram



Dimensional drawing



7/8" flush-type plug

Approvals

Approvals

Approvals

EAC

Flush-type connector - SACC-DSI-MINMS-5CON-UNF PCB - 1457487

Approvals

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------



Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>