



Order code: DK-2611-xx

No.	Specifications	Qty.
1	Ø3.0mm OM1 62.5/125 Duplex Cable / LSZH / Orange	1
2	3.0mm ST/PC MM Connector / Silver	4
3	ST 3.0mm Boot / Black	2
4	ST 3.0mm Boot / Red	2
5	Heatshrink Tube / Black	2

Performance:
 a. Insertion Loss: < 0.3dB
 b. Return Loss: > 20dB
 c. Fiber Extension: -100nm<H<+100nm
 d. Ferrule End-Face Radius: 10<R<25mm
 e. Apex Offset: ≤50um
 f. Increase in insertion Loss after 500 mating: 0.2 dB Max
 g. Operation Temperature: -40°C to +70 °C
 h. Storage Temperature: -40°C to +80 °C

P/N	Length (M)
01	1
03	3
05	5
07	7
10	10

RoHS compliant
Unit: mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE					Drawn	08.30.2017	Fred	ASSMANN WSW-No. DK-2611-xx
					Approved	08.30.2017	Fred	
DIM	TOL							Drawing-No.
								ASS 8061 CA
Angle	TOL	Id.	Modification	Date	Name			rev00
								Replace