

## Fuse plug - PV-C-M/F-PRO/F-1500/10-EU - 1622147

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse connector for protecting modules and devices in photovoltaic systems, black, SUNCLIX pin connector pattern, 1500 V/10 A, IP68 (24 h/2 m)

SUNCLIX fuse connector, in the version for 1500 V system voltage

### Product Description

SUNCLIX fuse connector, for 1500 V system voltage, fuse-link nominal current of 10 A, EU version

### Why buy this product

- One-piece design
- Robust, easy-to-install fuse element for outdoor use
- High-quality fuse-link
- Degree of protection: IP68 (24 h/2 m)
- 
- 1500 V



### Key Commercial Data

Packing unit	8 STK
Minimum order quantity	8 STK
GTIN	
GTIN	4055626130583

### Technical data

#### Ambient conditions

Degree of protection (when plugged in)	IP66 / IP68 (2 m / 24 h)
Ambient temperature (operation)	-40 °C ... 50 °C

#### General

Rated voltage	1500 V
Fuse-link nominal current	10 A DC (Nominal current of the fuse-link)
Fuse adapter nominal current	10 A DC

# Fuse plug - PV-C-M/F-PRO/F-1500/10-EU - 1622147

## Technical data

### Material

Flammability rating according to UL 94	V0
--	----

### Standards and Regulations


Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Drawings

### Dimensional drawing



Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>