



Mallory Sonalert Products, Inc.

Part #:

ZA028MDMT6

Sales Outline Drawing

Revision:

D

Specifications:

| | | | | |
|------------------------|---|--|--|---|
| Sound Level Category: | Medium | Medium | Medium | Medium |
| Mode of Operation: | Continuous | Slow Pulse @ 1 PPS | Fast Pulse @ 10 PPS | Siren Sweep 3.3 - 4 kHz @ 5 Sweeps per Sec. |
| Loudness @ 2 FT: | 75 to 85 dB(A) Typ. | 75 to 85 dB(A) Typ. | 75 to 85 dB(A) Typ. | 75 to 85 dB(A) Typ. |
| Pulse Rate (PPS): | | 1 | 10 | 5 |
| Frequency: | 3900 ± 500 Hz | 3900 ± 500 Hz | 3900 ± 500 Hz | 3.3 - 4 kHz |
| Connection: | "+" to Positive, "-" to Ground | "+" to Positive, "-" and "1" to Ground | "+" to Positive, "-" and "2" to Ground | "+" to Positive, "-", "1" and "2" to Ground |
| Voltage Rating: | 16 to 28 VDC | | | |
| Current Draw: | 40mA MAX | | | |
| Housing Material: | 6/6 Nylon, Color: Black | | | |
| Storage Temperature: | -40° to +80° C | | | |
| Operating Temperature: | -30° to +65° C | | | |
| Panel Mounting: | Recommended hole size is 22.5 mm. Thread front will fit standard 22.5mm hole. | | | |
| Knurled Nut: | Used to attach part to panel. The max recommended torque is 10 in-lbs. | | | |
| Weight (Typical): | 28 g | | | |
| NEMA 3R,4X, & 12: | Approved with use of ACC03. | | | |
| Options: | Please contact factory. | | | |

Dimensions: Inches (mm)

cUL Recognized

ROHS Compliant

