

Mounting set for securing the batteries - BATTERY MOUNTING CASE - 2320458

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Used for mounting batteries that cannot be mounted on DIN rails.




Product Description

Mounting set, consisting of battery frame for universal wall mounting or surface mounting, 2 x cross dowel (M6) with collar, 2 x screw (M6 x 140), 2 x washer (6.4 x 12), 1 x battery retaining bracket with fixing bracket, and 4 x screw (M3 x 14).



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 933131
GTIN	4046356933131

Technical data

General

Net weight	5 kg
------------	------

Dimensions

Width	464 mm
Height	201 mm
Depth	205 mm

Standards and Regulations

Shock	IEC 60068-2-27
Vibration (operation)	DNV GL

Approvals

Approvals

Mounting set for securing the batteries - BATTERY MOUNTING CASE - 2320458

Approvals

Approvals

ABS / BV / DNV GL / LR


Ex Approvals

Approval details

ABS	http://www.eagle.org/eagleExternalPortalWEB/	15-GD1438179-PDA
-----	---	------------------

BV		http://www.veristar.com/portal/veristarinfo/generalinfo/approved/approvedProducts/equipmentAndMaterials	41516/A0 BV
----	---	---	-------------

DNV GL	http://exchange.dnv.com/tari/	61457-13 HH
Nominal voltage UN	500 V	
Nominal current IN	41 A	
mm ² /AWG/kcmil	6	

LR		http://www.lr.org/en	17/20032
----	---	---	----------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>