

## SUMMARY

### # Wires

Low	0
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0

*Image is for illustrative purpose only*

### Download

[Request a quote](#)

[Catalog](#)

Series	3Y
Termination type	HV contact
IP rating	50
Cable Ø	0.00 - 0.00 mm
Matching parts	FFR.3Y.425.CFAE55G
Status	
Alternative part	

## TECHNICAL DETAILS

### Mechanics

Shell Style/Model	ERA*: Fixed receptacle, nut fixing
Keying	Circular (can rotate)
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing	∅ 0 - 0 mm
Variant	

### Performance

Configuration	3Y.425 : 1 High Voltage
Insulator	L: PEEK (UL 94 / V-0/3.2, depends on material thickness)
Rated Current	8 Amps

### Specifications

Contact Type:	Solder
Test voltage (kV DC)	52
Test voltage (kV AC)	37
Creepage dist. (mm):	25.5

### Others

## DRAWINGS

### Draws

### Dimensions

	A	E	L	M	e
mm.	31	16	50	6.5	M24x1.0
in.	1,22	0,63	1,97	0,26	

---

## RECOMMENDED BY LEMO

### Tools

None

### Cables