



MSTBW 2,5/ 5-GF-5,08 6,03 ABAU

Order No.: 1845109

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1845109>

Header, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 5, Pitch: 5.08 mm, Color: gray, Metal surface: Au, Assembly: Soldering, Gold-plated contact surface / color: Gray RAL 7038

Commercial data

| | |
|----------------|-------------------------------------------------------------------------------------------------------|
| GTIN (EAN) |  4 017918 217457 |
| Note | Made-to-order |
| sales group | E110 |
| Pack | 50 pcs. |
| Customs tariff | 85366990 |

Product notes

WEEE/RoHS-compliant since:
01/01/2003



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals

Certification

CSA, CUL, UL

Accessories

| Item | Designation | Description |
|---------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Assembly | | |
| 1755477 | MSTB-BL | Keying cap, for forming sections, plugs onto header pin, green insulating material |
| Marking | | |
| 0804293 | SK 5,08/3,8:FORTL.ZAHLEN | Marker card, printed horizontally, self-adhesive, 12 identical decades marked 1-10, 11-20 etc. up to 91-(99)100, sufficient for 120 terminal blocks |
| Plug/Adapter | | |
| 1734401 | CR-MSTB | Coding section, inserted into the recess in the header or the inverted plug, red insulating material |

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;