



# National MM58274CV 20-Pin PLCC-to-16-Pin DIP Pkg Converter

## FEATURES


- Pb-free RoHS/WEEE-compliant
- A cost-effective means of upgrading to a PLCC package type Clock Chip without changing your PCB layout.

## GENERAL SPECIFICATIONS

- BOARD MATERIAL: 0.062 thick FR-4 or IS410 per IPC 4101C/26 with 1-oz. Cu traces, both sides
- PADS: finished with ENIG (Immersion Au over Electroless Ni)
- PINS: 1/2-hard Brass 360 per UNS C36000, ASTM B16/B16M
- PIN PLATING: 10µ [0.25µ] min. Au per MIL-G-45204 over 100µ [2.54µ] Ni per SAE AMS-QQ-N-290
- OPERATING TEMPERATURE: 221°F [105°C] max.

## MOUNTING CONSIDERATIONS

- SUGGESTED PCB HOLE SIZE: 0.028 ±0.003 [0.71 ±0.08] dia.




**CUSTOMIZATION:** In addition to the standard products shown on this page, Aries specializes in custom design and production. Special materials, platings, sizes, and configurations can be furnished, depending on the quantity. **NOTE:** Aries reserves the right to change product general specifications without notice.

ALL DIMENSIONS: INCHES [MILLIMETERS]  
 ALL TOLERANCES: ±0.005 [0.13] UNLESS OTHERWISE SPECIFIED  
 THE ABOVE SHOWS CHIP MOUNTED FOR ILLUSTRATION PURPOSES ONLY. PLEASE CONTACT ARIES CUSTOMER SERVICE IF YOU WOULD LIKE TO SUPPLY THE CHIP OR HAVE ARIES SUPPLY AND MOUNT IT.  
 CONSULT FACTORY FOR OTHER SIZES AND CONFIGURATIONS

## ORDERING INFORMATION

**16-307349-11-RC-P**

Optional Panelized Version



20 PLCC Pin	TO	16-Pin DIP Pin
1	>	1
2	>	2
3	>	3
4	>	N/C
5	>	N/C
6	>	4
7	>	5
8	>	N/C
9	>	6
10	>	7
11	>	8
12	>	9
13	>	10
14	>	11
15	>	12
16	>	N/C
17	>	13
18	>	14
19	>	15
20	>	16



Bristol, PA 19007-6810 USA  
 TEL (215) 781-9956 • FAX (215) 781-9845  
 WWW.ARIESELEC.COM • INFO@ARIESELEC.COM



18101RC  
Rev. AA