	I G -	n m		0			
4	R 22.6 Max () () () () () () () () () () () () ()			<image/> <image/>	۲		
	K	Xeying Shown as example					
	-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy	Connector dimension           Dim         Nominal           A         34.9±0.3           B         19.07+0.1/-0.15           R         32.5Max           S         31.8±0.4           W         2.2+0.9/-0.1           VV THREAD         M15x1-6g		SOURIAU shall not be liable for any non-co due to a use of the Products which doe the Specifications issued by either of the Par (professional recommendation, tecl	s not comply with ties or by a third party		
N	<ul> <li>-Seals &amp; Grommet : Silicon Elastomer</li> <li>-Contact Plating : Gold over copper Alloy 0.8µm minimum</li> <li>-Durability : 500 Mating cycles</li> <li>-Delivered with Souriau contacts and Accessories</li> </ul>			PN: 8D711W05A	Jurisdiction & Control List Not Listed 2		
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours A 01-10-2016 First Release						
_	-Mass : 19.48 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	MOD N° CUSTOMER DRAWING		
			TITLE	Aluminium Rece	eptacle 8D series		
	BASIC SERIES:8D7-11W05SHELL TYPE : Jam nut Receptacle </td <td>A C</td> <td>SCALE -{</td> <td>General linear Tolerances:</td> <td>NPRDS / PROJECT 859</td>	A C	SCALE -{	General linear Tolerances:	NPRDS / PROJECT 859		
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORIENTATION : C CONTACT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURIAU.COM	This document is the property of SOURIAU it must not be reproduced or communicated without permission		
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 11-05	FORMAT A3	SOURIAU DRO 8D711W05A0	G N° SHEET		
L	H G I	F E	D	C B			

-	D I		п		0 0		
4	Contact Layout x x x x x x x x			MAL	Panel cutout		4
	Contacts (Insert arrangement 11-5)           Contact position         Contact location position           D         Contact (mm)         Y-axis (mm)         Y-axis (mm)           A         +.065 (1.65)         +.056 (1.42)           B         +.113 (2.87)        065 (1.65)           C         +.000 (0.00)        130 (3.30)           D        113 (2.87)        065 (1.65)           E        065 (1.65)         +.056 (1.42)           Shell         Arrangement no.         Number of contacts         Size contacts         Service rating         Contact location           11         -5         5         20         I         All         MS20050-5				ØC		
ω		1			DimNominalB19.59+0/-0.25ØC20.96+0.25/-0		3
					SOURIAU shall not be liable for any non-com due to a use of the Products which does r the Specifications issued by either of the Partie (professional recommendation, techn	not comply with es or by a third party	
N					PN: 8D711W05A	Jurisdiction & Control List Not Listed	2
				A 01-10-2016 Find the second s	Latest modification - by Date: Aluminium Recep	CUSTOMER DRAWING	
1				SCALE NA SOURIAU	General linear Tolerances: ± WWW.SOURIAU.COM	NPRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or communicated without permission	1
				FORMAT A3	SOURIAU DRG 8D711W05AC	N° SHEET	
L	H G	F	E	D	C B	Α	