



Pitch, Unguided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.50mm, Plated  
Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551604  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.90mm, Plated  
Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551605  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
5.50mm, Plated  
Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551606  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.50mm, Plated  
Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761551608  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
5.50mm, Plated  
Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761551613  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Left Endwall, 16  
Columns, 192  
Circuits, Pin Length  
4.50mm, Plated

Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551614  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Left Endwall, 16  
Columns, 192  
Circuits, Pin Length  
4.90mm, Plated

Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551615  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Left Endwall, 16  
Columns, 192  
Circuits, Pin Length  
5.50mm, Plated

Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551616  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Left Endwall, 16  
Columns, 192  
Circuits, Pin Length  
4.50mm, Plated

Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761551617  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Left Endwall, 16  
Columns, 192  
Circuits, Pin Length  
4.90mm, Plated

Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761551618  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Left Endwall, 16  
Columns, 192  
Circuits, Pin Length  
5.50mm, Plated

Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761551623  
4 Pair Vertical

Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Dual Endwall, 16  
Columns, 192  
Circuits, Pin Length  
4.50mm, Plated  
Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551624  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Dual Endwall, 16  
Columns, 192  
Circuits, Pin Length  
4.90mm, Plated  
Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551625  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Dual Endwall, 16  
Columns, 192  
Circuits, Pin Length  
5.50mm, Plated  
Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551626  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Dual Endwall, 16  
Columns, 192  
Circuits, Pin Length  
4.50mm, Plated  
Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761551627  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Dual Endwall, 16  
Columns, 192  
Circuits, Pin Length  
4.90mm, Plated  
Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761551628  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Dual Endwall, 16  
Columns, 192

Circuits, Pin Length  
5.50mm, Plated  
Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761551633  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Right Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.50mm, Plated  
Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551634  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Right Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.90mm, Plated  
Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551635  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Right Endwall,  
16 Columns, 192  
Circuits, Pin Length  
5.50mm, Plated  
Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761551636  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Right Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.50mm, Plated  
Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761551637  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Right Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.90mm, Plated  
Through Hole  
Dimension 0.39mm,  
Lead-Free

Impact™ 100 Ohm	0761551638
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Unguided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
Impact™ 100 Ohm	0761553603
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	
Impact™ 100 Ohm	0761553604
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead-Free	
Impact™ 100 Ohm	0761553605
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	
Impact™ 100 Ohm	0761553606
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
Impact™ 100 Ohm	0761553607
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided,	

Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.90mm, Plated  
Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761553608  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Left Guided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
5.50mm, Plated  
Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761553618  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Left Guided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
5.50mm, Plated  
Through Hole  
Dimension 0.39mm ,  
Orientation Key A,  
Lead-Free  
Impact™ 100 Ohm 0761555603  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.50mm, Plated  
Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761555604  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.90mm, Plated  
Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761555605  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
5.50mm, Plated

Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0761555606  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.50mm, Plated

Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761555607  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.90mm, Plated

Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761555608  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
5.50mm, Plated

Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0761555618  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Open Endwall,  
16 Columns, 192  
Circuits, Pin Length  
5.50mm, Plated

Through Hole  
Dimension 0.39mm ,  
Orientation Key A,  
Lead-Free  
Impact™ 100 Ohm 0761557603  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Left Guided,  
Right Endwall,  
16 Columns, 192  
Circuits, Pin Length  
4.50mm, Plated

Through Hole  
Dimension 0.46mm,  
Lead-Free



Impact™ 100 Ohm	0761557604
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead-Free	
Impact™ 100 Ohm	0761557605
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	
Impact™ 100 Ohm	0761557606
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
Impact™ 100 Ohm	0761557607
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
Impact™ 100 Ohm	0761557608
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided, Right Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	
Impact™ 100 Ohm	0761557618
4 Pair Vertical Backplane Header, 1.90 by 1.35mm Pitch, Left Guided,	

Right Endwall,  
16 Columns, 192  
Circuits, Pin Length  
5.50mm, Plated  
Through Hole  
Dimension 0.39mm ,  
Key Orientation A,  
Lead-Free  
Impact™ 100 Ohm 0761558604  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Left Endwall, 16  
Columns, 192  
Circuits, Pin Length  
4.90mm, Plated  
Through Hole  
Dimension 0.46mm,  
Tin (Sn) Lead (Pb)  
Impact™ 100 Ohm 0761558605  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Left Endwall, 16  
Columns, 192  
Circuits, Pin Length  
5.50mm, Plated  
Through Hole  
Dimension 0.46mm,  
Tin (Sn) Lead (Pb)  
Impact™ 100 Ohm 0761558607  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Left Endwall, 16  
Columns, 192  
Circuits, Pin Length  
4.90mm, Plated  
Through Hole  
Dimension 0.39mm,  
Tin (Sn) Lead (Pb)  
Impact™ 100 Ohm 0761558608  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Left Endwall, 16  
Columns, 192  
Circuits, Pin Length  
5.50mm, Plated  
Through Hole  
Dimension 0.39mm,  
Tin (Sn) Lead (Pb)  
Impact™ 100 Ohm 0761559603  
4 Pair Vertical  
Backplane Header,  
1.90 by 1.35mm  
Pitch, Right Guided,  
Left Endwall, 16  
Columns, 192  
Circuits, Pin Length  
4.50mm, Plated

Through Hole  
Dimension 0.46mm,  
Lead-Free

This document was generated on 04/04/2013

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**