

Radial Leaded Inductors[LHL]

LHL16TB222J



■ Features

- Item Summary
2200uH±5%, 0.6A, φ 17.0x21.0mm Radial
- Lifecycle Stage
Discontinued
- Standard packaging quantity (minimum)
Taping 250pcs

■ Products characteristics table

Inductance	2200 uH ± 5 %
Case Size (mm)	17.0x21.0
Rated Current (max)	0.6 A
DC Resistance (max)	1.4 Ω
Q (min)	20
LQ Measuring Frequency	0.252 MHz
Self Resonant Frequency (min)	0.56 MHz
Operating Temp. Range	-25 to +105 °C (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 7 %
RoHS2 Compliance (10 subst.)	Yes
Soldering	Wave

■ External Dimensions

Dimension D	Max φ 17.0 mm
Dimension H2	Max 21.0 mm
Dimension d	φ 0.8 ±0.05 mm
Dimension F	7.5 ±1.0 mm
Dimension l	5.0 ±1.0 mm

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.