



- CONNECTOR DIMENSIONS ARE PER ARINC 600 SPECIFICATION
- KEYING SHOWN IN POSITION "01" FOR REFERENCE ONLY. SEE TABLE FOR KEYING POSITION. FOR POSITION "00" KEYING SHIPPED UNASSEMBLED.

COMPONENT	MATERIAL	FINISH
SHELL	DIE CAST ALUMINUM PER ASTM-B-85	ELECTROLESS NICKEL PER MIL-C-26074.
RETENTION PLATES	ALUMINUM ALLOY PER ASTM-B-209	ELECTROLESS NICKEL PER MIL-C-26074.
SCREWS AND LOCKWASHERS	STEEL OR STAINLESS STEEL	CHROMATE OVER ZINC OR PASSIVATED
POLARIZING POSTS	ZINC ALLOY PER ASTM-B-86	ELECTROLESS NICKEL PER MIL-C-26074.
INSERTS	THERMOSET	-
EMI GROUND SPRING	BERYLLIUM COPPER 172 (ALLOY 29)	ELECTRODEPOSITED NICKEL PER QQ-N-290
GROMMET	FLUOROSILICONE	-
POLARIZING POST RETAINING PLATE	ALUMINUM ALLOY PER ASTM-B-209	BLUE ANODIZED PER MIL-A-8625

08	MODULE A 208262-3 (SIZE 22 PIN CONTACT; QTY=150)	1663346-1
	MODULE B 208267-2 (SIZE 22 SOCKET CONTACT; QTY=60)	
KEYING POSITION	CONTACTS INCLUDED NOT INSTALLED	PART NUMBER

  

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWG: C.C.THOMAS 10-25-04		Tyco Electronics Corporation	
DIMENSIONS: INCHES		CHK: K.HOGAN 10-26-04		Harrisburg, Pa 17105-3608	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APP'D: K.HOGAN 10-26-04		NAME: PLUG ASSY, SIZE 2, ARR 262ARINC 600, (150/60/34)	
0 PLC ± .005		PRODUCT SPEC: -		NIC66HN262F08AA0	
1 PLC ± .005		APPLICATION SPEC: -		SIZE: A1	
2 PLC ± .005		WEIGHT: -		CAGE CODE: 00779	
3 PLC ± .005		CUSTOMER DRAWING		DRAWING NO: 1663346	
4 PLC ± .005		SCALE: 1.5:1		SHEET 1 OF 1	
ANGLES ± .005		REV: B			