


NOTE 1. The procedure of cable assemblies would be confirm.
 2. When this plug is mated with a MF10S receptacle,
 the clamp torque of the part No. ② should be 1.5 to 3 N·m.
 Following MF10-T1 can be used as simple
 substitution of a torque wrench.

EXCLUSIVE PLASTIC SPANNER	PART NO.	CODE NO.
	MF10-T1	CL709-0205-8

③ The ferrule parts are not contained.
 Please use the 'standard MU ferrule' chosen from
 the outer diameter of the optical fiber.

NO.	MATERIAL	FINISH .	REMARKS	NO.	MATERIAL	FINISH .	REMARKS
7	BRASS	NICKEL PLATING		14	ZIRCONIA		
6	NBR RUBBER	COLOR:BLACK		13	STAINLESS STEEL		
5	NBR RUBBER	COLOR:BLACK		12	STAINLESS STEEL	NYELOCK	
4	ZINC DIECAST	NICKEL PLATING		11	ALUMINIUM ALLOY	ANODIC OXIDE COATING	
3	BRASS	NICKEL PLATING		10	STAINLESS STEEL		
2	BRASS	NICKEL PLATING		9	PPS RESIN	COLOR:BLACK	
1	ZINC DIECAST	NICKEL PLATING		8	NBR RUBBER	COLOR:BLACK	

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△				
APPROVED : MT. SHIBUTANI			18.02.02	DRAWING NO. EDC-178954-31-00		
CHECKED : FS. YOSHIDA			18.02.02	PART NO. MF10S-WPN7C50-0200(31)		
DESIGNED : TY. SATO			18.02.02	CODE NO. CL709-0214-9-31		
DRAWN : MK. INOUE			18.02.01	1/1		