

## Printed-circuit board connector - PTSM 0,5/ 2-HHI-2,5-SMD R24 - 1810719

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Header, Nominal current: 6 A, Rated voltage (III/2): 160 V, Number of positions: 2, Pitch: 2.5 mm, Color: black, Contact surface: Tin, Assembly: Taped SMD/THT/THR components

The figure shows a 3-pos. version of the product



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 500 pc   |
| Weight per Piece (excluding packing) | 1.52 GRM |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|             |        |
|-------------|--------|
| Pitch       | 2.5 mm |
| Dimension a | 2.5 mm |

#### General

|                             |                     |
|-----------------------------|---------------------|
| Range of articles           | PTSM 0,5/..-HHI-SMD |
| Insulating material group   | IIIa                |
| Rated surge voltage (III/3) | 2.5 kV              |
| Rated surge voltage (III/2) | 2.5 kV              |
| Rated surge voltage (II/2)  | 2.5 kV              |
| Rated voltage (III/3)       | 63 V                |
| Rated voltage (III/2)       | 160 V               |
| Rated voltage (II/2)        | 160 V               |
| Nominal current $I_N$       | 6 A                 |
| Maximum load current        | 6 A                 |

# Printed-circuit board connector - PTSM 0,5/ 2-HHI-2,5-SMD R24 - 1810719

## Technical data

### General

|   |       |
|---|-------|
| Insulating material                     | LCP   |
| Inflammability class according to UL 94 | V0    |
| Color                                   | black |
| Number of positions                     | 2     |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27141190 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002638 |
| ETIM 5.0 | EC002637 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

## Approvals

### Approvals

---

Approvals

GOST / UL Recognized

---

Ex Approvals

---

# Printed-circuit board connector - PTSM 0,5/ 2-HHI-2,5-SMD R24 - 1810719

## Approvals

Approvals submitted


## Approval details

GOST

|                                |       |
|--------------------------------|-------|
| UL Recognized                  | B     |
| Nominal current I <sub>N</sub> | 5 A   |
| Nominal voltage U <sub>N</sub> | 150 V |

## Drawings

Drilling diagram



Dimensioned drawing

