


## Specification Sheet

Part Number: 553-50004



Heat Shrink Labels, Single Side, 1-Slit, .125" (3.17mm), PO-X, White, 500/box

Article Number	553-50004
Type	HST3-1WH-S
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none"><li>• Slide Slit and optional center slits for easy wire insertion.</li><li>• Smooth surface for clean and legible printing.</li><li>• Supplied on a ladder style carrier so that markers can be kitted after printing.</li><li>• A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.</li></ul>
Quantity Per	box

### Product Description

HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

<b>Short Description</b>	Heat Shrink Labels, Single Side, 1-Slit, .125" (3.17mm), PO-X, White, 500/box
<b>Global Part Name</b>	HST3-1WH-S-PO-X-WH
<b>Variant</b>	Thin-Wall
<b>Width W (Imperial)</b>	0.95
<b>Width W (Metric)</b>	24.13
<b>Thickness T (Imperial)</b>	.003
<b>Thickness T (Metric)</b>	.0762
<b>Height H (Imperial)</b>	0.235
<b>Height H (Metric)</b>	5.69
<b>Width of Liner (Metric)</b>	76.2
<b>Width of Liner (imperial)</b>	3.0
<b>Outside Diameter OD(Imperial)</b>	0.125
<b>Outside Diameter OD(metric)</b>	3.2
<b>Outside Diameter Max(Imperial)</b>	0.125
<b>Outside Diameter Max (metric)</b>	3.2
<b>Wall Thickness WT (Imperial)</b>	0.0209
<b>Wall Thickness WT (Metric)</b>	0.53

<b>Material</b>	Polyolefin, cross-linked (PO-X)
-----------------	---------------------------------

**Material Shortcut** PO-X

<b>US MIL SPEC</b>	AMS-DTL-23053/5 Class 1 and 3
--------------------	-------------------------------

MIL-STD-202G Method 215K  
SAE-AS81531

**Flammability**

UL 224 VW-1

**Halogen free**

No

**Operating Temperature (Metric)**

-67°F to +275°F (-55°C to +135°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Certification/Specification WEB**

UL 224 125 °C 600V VW-1

<b>Package Quantity(Imperial)</b>	500
-----------------------------------	-----

**Package Quantity (Metric)** 500

<b>Customs Number</b>	3926909987
-----------------------	------------

**Content Unit(BMEcat)** pack

<b>Labels per Column</b>	1
--------------------------	---

**Labels per Row** 2

**Weight (Metric)** 0.294

**Weight (Imperial)** 0.64