

(0.80 mm) .0315"

QTE SERIES

# HIGH-SPEED GROUND PLANE HEADER

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com/QTE](http://www.samtec.com/QTE)


- Insulator Material:** Liquid Crystal Polymer
- Terminal Material:** Phosphor Bronze
- Plating:** Au or Sn over 50 μ" (1.27 μm) Ni
- Current Rating:** Contact: 2 A per pin (1 pin powered per row) Ground Plane: 23 A per ground plane (1 ground plane powered)
- Operating Temp Range:** -55 °C to +125 °C
- Voltage Rating:** 225 VAC mated with QSE & 5 mm Stack Height
- Max Cycles:** 100
- RoHS Compliant:** Yes

**Board Mates:**  
QSE

**Cable Mates:**  
EQCD, EQDP  
(See Also Available Note)

**Standoffs:**  
SO

Integral metal plane for power or ground



Standard stack heights from 5 mm to 25 mm

## HIGH-SPEED CHANNEL PERFORMANCE

QTE-DP/QSE-DP @ 5 mm Mated Stack Height  
Rating based on Samtec reference channel.  
For full SI performance data visit [Samtec.com](http://Samtec.com) or contact [SIG@samtec.com](mailto:SIG@samtec.com)

28  
Gbps



## PROCESSING

- Lead-Free Solderable:** Yes
- SMT Lead Coplanarity:** (0.10 mm) .004" max (020-060)
- Board Stacking:** For applications requiring more than two connectors per board contact [ipg@samtec.com](mailto:ipg@samtec.com)

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



## PROTOCOLS

- 100 GbE
- XAUI
- PCI Express®
- SATA
- MGT (Rocket I/O)
- InfiniBand™

## ALSO AVAILABLE (MOQ Required)

- 15 mm, 22 mm and 30 mm stack height
  - 30 μ" (0.76 μm) Gold (Specify -H plating for Data Rate cable mating applications.)
  - Edge Mount, Guide Posts, Screw Down & Friction Lock
  - 56 (-DP), 80, 100 positions per row
  - Retention Option
- Contact Samtec.



-020, -040, -060  
(40 total pins per bank = -D)  
-014, -028, -042  
(14 pairs per bank = -D-DP)





Specify LEAD STYLE from chart

-F = Gold Flash on Signal Pins and Ground Plane, Matte Tin on tails  
-L = 10 μ" (0.25 μm) Gold on Signal Pins and Ground Plane, Matte Tin on tails

-D = Single-Ended  
-D-DP = Differential Pair (-01 only)

-K = (7.00 mm) .275" DIA Polyimide Film Pick & Place Pad  
-TR = Tape & Reel Packaging (N/A -05 & -07 lead style)

-L = Latching Option (N/A on -042 & -060 positions)



-C\* = Electro-Polished Selective  
50 μ" (1.27 μm) min Au over 150 μ" (3.81 μm) Ni on Signal Pins in contact area, 10 μ" (0.25 μm) min Au over 50 μ" (1.27 μm) Ni on Ground Plane in contact area, Matte Tin over 50 μ" (1.27 μm) min Ni on all solder tails

\*Note: -C Plating passes 10 year MFG testing

Note: Some lengths, styles and options are non-standard, non-returnable.

QTE LEAD STYLE	A	HEIGHT WITH QSE*
-01	(4.27) .168	(5.00) .197
-02	(7.26) .286	(8.00) .315
-03	(10.27) .404	(11.00) .433
-04	(15.25) .600	(16.00) .630
-05	(18.26) .718	(19.00) .748
-07	(24.24) .954	(25.00) .984
-09	(13.26) .522	(14.00) .551

\*Processing conditions will affect mated height. See SO Series for board space tolerances