

# Spec Sheet

Multilayer Chip Inductors for Automotive / Industrial Applications (LK series)

## LK1005R68K-TV



### ■ Features

- Item Summary  
0.68uH±10%, 20mA, 0402/1005 (EIA/JIS)
- Lifecycle Stage  
Mass Production
- AEC-Q200 qualified
- Standard packaging quantity (minimum)  
Taping paper 10000pcs

### ■ Products characteristics table

|                               |                |
|-------------------------------|----------------|
| Inductance                    | 0.68 uH ± 10 % |
| Case Size (EIA/JIS)           | 0402/1005      |
| Rated Current (max)           | 20 mA          |
| DC Resistance (max)           | 0.55 Ω         |
| Q (min)                       | 20             |
| LQ Measuring Frequency        | 10 MHz         |
| Self Resonant Frequency (min) | 70 MHz         |
| Operating Temp. Range         | -40 to +85 °C  |
| RoHS2 Compliance (10 subst.)  | Yes            |
| REACH Compliance (173 subst.) | Yes            |
| Halogen Free                  | Yes            |
| Soldering                     | Reflow         |

### ■ External Dimensions

|             |              |
|-------------|--------------|
| Dimension L | 1.0 ±0.05 mm |
| Dimension W | 0.5 ±0.05 mm |
| Dimension T | 0.5 ±0.05 mm |
| Dimension e | 0.25 ±0.1 mm |

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
Before making final selection, please check product specification.

2017.04.30