

Specification Sheet

Part Number: T30RA3000



Cable Ties for AT2060, 30lb Tensile Strength, PA66, Natural, 3000/reel

Article Number

103-00001

Type

T30RA

Color

Natural (NA)

Features & Benefits

- The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.
- Available in reels of 3,000 each or bandoliers of 30 each.

Quantity Per

reel

Product Description

Cable ties for use with HellermannTyton's AT2060 automatic cable tie tool

Short Description

Cable Ties for AT2060, 30lb Tensile Strength, PA66, Natural, 3000/reel

Global Part Name

T30RA-PA66-NA

Minimum Tensile Strength (Imperial)	30.0
Minimum Tensile Strength (Metric)	135.0
Length L (Imperial)	6.0
Length L (Metric)	152.4
Identification Plate Position	none
Reel Diameter (Imperial)	17.7
Reel Diameter (Metric)	450.0
Reel Width (Imperial)	7.197
Reel Width (Metric)	182.8
Voltage Range	27 Volt
Releasable Closure	No
Width W (Imperial)	0.14
Width W (Metric)	3.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.25
Bundle Diameter Max (Metric)	31.75

Thickness T (Imperial) 0.05

Thickness T (Metric) 1.2

Cycle Time 1.2 seconds

Power Supply Electrical

Tension Force Adjustable

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

US MIL SPEC MS3367-5-9

SAE-AS33671

Flammability

UL 94 V2

-40°F to +185°F (-40°C to +85°C)

CAGE Code 53421 UL-ZODZ2.E64139

Yes

Yes

Package Quantity(Imperial) 3000

Operating Temperature (Metric)

Certification/Specification WEB

UL Recognized (US)

UL Recognized (US and Canada)

Package Quantity (Metric) 3000

Customs Number 3926909987

Weight (Metric) 1.8

Weight (Imperial) 3.9

Reel Weight (Imperial) 7

Reel Weight (Metric) 3.175