



D see data sheet cable

Technical specification:

Rated voltage: IEC 61076-2-101	8pos 30 V
Current rating: IEC 61076-2-101	2 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	>=100

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Coupling screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

Installation specification:

Recommended torque:	0,6 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 13: 36-000220

Contact assignment:

1 - white	5 - grey
2 - brown	6 - pink
3 - green	7 - blue
4 - yellow	8 - red

Part no:	Description:	Length L:	Cable:
43-11062	SAL - 12 - RS8 - 2 / K1	2m	TPU, UL 20549, black, 8x0,25mm ² Cable: 781-K12800
43-11063	SAL - 12 - RS8 - 3 / K1	3m	
43-11064	SAL - 12 - RS8 - 5 / K1	5m	
43-11065	SAL - 12 - RS8 - 10 / K1	10m	
43-xxxxx	SAL - 12 - RS8 - ... / K1	x	

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: b 24.01.2011 VF Ä3767 Coupling screw modified, spanner flats added, data sheet modified	dim. in mm	title: Male connector M12x1 axial		
					date
	tolerance of cable: L <= 4m: L + 40mm L > 4m: L + 1%	drawn 14.03.07 appd. 14.03.07	Mankopf Fromm	dwg no: 43K1A404	
	general tolerance: 0 ± 0,50mm 0,0 ± 0,25mm 0,00 ± 0,10mm				
	<small>THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH</small>				