

Specification Sheet

Part Number: 169-60019



Convoluted Tubing, Slit, .5" Dia, PA6, Black with Gray Stripe, 100 ft/pkg

Article Number	169-60019
Type	CTN120
Color	Black with Gray Stripe (BKSTGY)
Features & Benefits	<ul style="list-style-type: none">• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture• Tubing protects cables and wires against automotive fluids, vibration wear• Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight
Quantity Per	box

Product Description

HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

Short Description

Convoluted Tubing, Slit, .5" Dia, PA6, Black with Gray Stripe, 100 ft/pkg

Global Part Name

CTN120-PA6-BK

Technical Description

Convoluted Tubing, Slit, 1/2" Dia., PA6, Black w/Gray Stripe

Length L (Imperial)

100.0

Length L (Metric)

30.5

Width W (Imperial)

0.127

Inner Diameter D (Imperial)

0.516

Inner Diameter D (Metric)

13.11

Diameter D (imperial)

0.70

Diameter D (metric)

17.78

Outside Diameter OD(Imperial)

0.70

Outside Diameter OD(metric)

17.78

Nominal Diameter (Imperial)

0.5

Nominal Diameter (Metric)	12.70
Wall Thickness WT (Imperial)	.005
Wall Thickness WT (Metric)	0.127
Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	UL 94 HB
Halogen free	No
Operating Temperature (Metric)	-40°F to +300°F (-40°C to +149°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	3926909987

