



**NOTES:**

1. RoHS COMPLIANT
- ② 2. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
3. INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0, BLACK
4. CONTACTS: COPPER ALLOY  
PLATING: 8µin HARD GOLD over min. 50µin NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 20
5. CAPACITANCE: 180pF ± 20%
6. DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
7. CONNECTOR IS PART MARKED: 242A26760X CONEC ABC

Directive 2002/95/EC  
"RoHS"  
Compliant

|   |        |
|---|--------|
| APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL |        |
| CUSTOMER APPROVAL DATE:                                   |        |
| NAME:   | TITLE: |
| COMPANY NAME:   |        |
| APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL |        |

|  |             |            |        |
|--|-------------|------------|--------|
| THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH |             |            |        |
| DO NOT ALTER CAD DRAWING BY HAND   |             |            |        |
| 1 x b  | Ä 3387      | 15.07.2009 | Petker |
| a  | Origin      |            |        |
| rev.   | description | date       | name   |

|           |                  |   |             |            |
|-----------|------------------|---|-------------|------------|
| tolerance | dim. in mm       | scale:  | 2:1 (5:1)   |            |
|           |                  | material:   | SEE NOTES   |            |
| date      | name             | title:<br><b>D-SUB FILTER FEMALE</b><br>25pos. SOLDER CUP |             |            |
| drawn     | 30.06.09 Petker  |   |             |            |
| appd.     | 01.07.09 Fischer |   |             |            |
| norm      |                  |   |             |            |
| d-old     |                  | dwg no:   | Inventor 10 | DIN-A3     |
|           |                  |   | 24K1A1182   | sh: 1      |
|           |                  |   | part no:    | 242A26760X |

